

KT inserts

KT cable entry inserts small KT 3 to KTS 17



Specification KT colour grey:

Material: Elastomer
UL-94 V0, self-extinguishing,
halogen-free, silicone-free,
Protection to IP 54

Specification KT colour black:

Material: Elastomer
UL-94 HB, higher chemical resistance
Protection to IP 54

Type	Order No. grey	Order No. black	Clamping range	For insert small / large	PU
KT 3	41203	41303	3 – 4 mm	● / –	10
KT 4	41204	41304	4 – 5 mm	● / –	10
KT 5	41205	41305	5 – 6 mm	● / –	10
KT 6	41206	41306	6 – 7 mm	● / –	10
KT 7	41207	41307	7 – 8 mm	● / –	10
KT 8	41208	41308	8 – 9 mm	● / –	10
KT 9	41209	41309	9 – 10 mm	● / –	10
KT 10	41210	41310	10 – 11 mm	● / –	10
KT 11	41211	41311	11 – 12 mm	● / –	10
KT 12	41212	41312	12 – 13 mm	● / –	10
KT 13	41213	41313	13 – 14 mm	● / –	10
KT 14	41214	41314	14 – 15 mm	● / –	10
KT 15	41215	41315	15 – 16 mm	● / –	10
KTS 16	39901	39912	16 mm	● / –	10
KTS 17	39900	39913	17 mm	● / –	10
KT 2/4	39906	39907	2 x ø 4 mm	● / –	10
KT 2/5	41200	39904	2 x ø 5 mm	● / –	10
KT 2/6	41201	39905	2 x ø 6 mm	● / –	10
KT 2/7	41202	39916	2 x ø 7 mm	● / –	10
KT 4/3	39914	39915	4 x ø 3 mm	● / –	10
KT 4/4	39909	39911	4 x ø 4 mm	● / –	10
KT 4/5	39908	39910	4 x ø 5 mm	● / –	10
KT 4/6	39932	39933	4 x ø 6 mm	● / –	10
KT-ASI	39902	39903	for 1 ASI-cable	● / –	10
KT-ASI2	39922	39924	for 2 ASI-cables	● / –	10

KT cable entry inserts large KT 16 to KT 34



Specification KT colour grey:

Material: Elastomer
UL-94 V0, self-extinguishing,
halogen-free, silicone-free,
Protection to IP 54

Specification KT colour black:

Material: Elastomer, UL-94 HB, higher
chemical resistance, Protection to IP 54

Type	Order No. grey	Order No. black	Clamping range	For insert small / large	PU
KT 16	41216	41316	16 – 17 mm	– / ●	10
KT 17	41217	41317	17 – 18 mm	– / ●	10
KT 18	41218	41318	18 – 19 mm	– / ●	10
KT 19	41219	41319	19 – 20 mm	– / ●	10
KT 20	41220	41320	20 – 21 mm	– / ●	10
KT 21	41221	41321	21 – 22 mm	– / ●	10
KT 22	41222	41322	22 – 23 mm	– / ●	10
KT 23	41223	41323	23 – 24 mm	– / ●	10
KT 24	41224	41324	24 – 25 mm	– / ●	10
KT 25	41225	41325	25 – 26 mm	– / ●	10
KT 26	41226	41326	26 – 27 mm	– / ●	10
KT 27	41227	41327	27 – 28 mm	– / ●	10
KT 28	41228	41328	28 – 29 mm	– / ●	10
KT 29	41229	41329	29 – 30 mm	– / ●	10
KT 30	41230	41330	31 – 32 mm	– / ●	10
KT 32	41232	41332	32 – 33 mm	– / ●	10
KT 34	41234	41334	33 – 34 mm	– / ●	10

Blind inserts / Adapter inserts



Specification KT colour grey:
Protection to IP 54,
UL-94 V0, self-extinguishing,
halogen-free, silicone-free

Specification KT colour black:
Protection to IP 54,
UL-94 HB,
higher chemical resistance


Type	Order No. grey	Order No. black	Clamping range	For insert small / large	PU
BTK	41251	41351	Blind inserts small	• / –	10
BTG	41252	41352	Blind inserts large	– / •	10
ATG	41253	41353	Adapter inserts	– / •	10

Cable inserts multi-range

Don't you know the exact cable diameter of cables?

Utilizing KTMB multiple range-inserts the matching insert is always with you, for cable diameter up to 13.0 mm!

Cable inserts multiple range (not matching for pre-fabricated cables)



Cross section diagram

Type	Order No. grey	Clamping range	For insert small / large	PU
KTMB-A	41432	2.5 – 6.5 mm	• / –	10
KTMB-B	41434	4.0 – 7.5 mm	• / –	10
KTMB-C	41436	6.5 – 10.0 mm	• / –	10
KTMB-D	41438	9.5 – 13.0 mm	• / –	10
BTK	41251	Blind insert	• / –	10

Plugs

Place plugs in holes not equipped with cables.

If required, plugs can easily be removed and replaced with cables.

Plugs



Specification:
Colour white,
UL-94 V0, self-extinguishing,
halogen-free, silicone-free

Type	Order No.	D = Diameter in mm	L = Length in mm	PU
Plugs ST 3	42901	3	25	25
Plugs ST 4	42908	4	25	25
Plugs ST 5	42906	5	25	25
Plugs ST 6	42903	6	25	25
Plugs ST 7	42905	7	25	25
Plugs ST 8	42899	8	20	25
Plugs ST 9	42897	9	20	25
Plugs ST 10	42895	10	20	25
Plugs ST 11	42893	11	20	25
Plugs ST 12	42891	12	20	25
Plugs ST 13	42889	13	20	25
Plugs ST 14	42887	14	20	25
Plugs ST 15	42885	15	20	25
Plugs ST 16	42883	16	20	25
Plugs ST 17	42881	17	20	25